

Safariland Duty Gear Technical Specification Package

Model 6390 and 6395

General Description

Duty Holster for pistol handguns. Designed for use on a Safariland Sam Browne 2 ¼" (58mm) or 2" (50mm) belt. **6395 has a 1.5" (38 mm) drop belt loop with jacket slot for male and female use.** Duty holster includes installed hood guard.

Product Function

Maintains handgun in a stable, tactically ready configuration. Utilizes ALS® (Automatic Locking System) Retention system, and automatically secures weapon once holstered. A simple straight up draw is used once release is deactivated. This model is quick and easy to holster and secures the handgun with the ALS snap-free operation. This holster is an open-top design without SLS allowing for quick retrieval of weapon. This model comes standard as a Level I Retention™ holster. A wrap-around thermal-formed design with a specific hole pattern for installation of the optional ALS Guard, providing extra security and Level II Retention™ when deemed necessary. It also uses a tension device for handgun adjustment. The adjusting screw is accessed from the opening in the muzzle end of the holster. The UBL (Universal Belt Loop) is a friction style design, which is injection molded out of high impact resistant nylon. The holster is suede lined to protect handgun's finish.

Construction Materials

Lamination of polyurethane and synthetic suede non-woven: nylon micro fiber material for holster liner to assist with the protection of the handgun. The hood guard is mold-injected out of glass filled nylon. Case hardened nylon screws and T-Nuts are used as fastening devices. Must be able to withstand a minimum of 48 hours submerged in water and retain shape and function. Exterior material to pass minimum of 2000 cycles at 1000 gms on taber abrasion test with H18 wheels.

Available Finishes

STX Plain Black, STX Basket, STX Tactical® Black, STX Hi-Gloss

Available Belt Loops

Standard 2 ¼" (58mm) or 2" (50mm) Universal Belt Loop (UBL)

Manufacturing Process

Holster body is heat and pressure molded to fit specific weapon with wraparound, weltless construction. Sight channel is molded in. The beltloop is injection molded for body curvature. The hood guard and gun retention insert are mold-injected as well. All edges are sanded and burnished for a nice, smooth finish.

Dimensions and Weights:

	<u>Imperial</u>	<u>Metric</u>
Weight:	.67 lbs	.31 kg
Length:	10 ¼"	26.04 cm
Height:	3 3/8"	8.57 cm
Width:	4 1/8"	10.48 cm

Patent Information

6390 falls under patents: U.S. Pat. #7,694,860
Other patents pending

Quality Control

ISO 9001 Societe Generale de Surveillance – ANSI RAB Registrar AQS Quality Procedure.

Insurance Coverage

Safariland is insured with Product Liability coverage.

Safariland, LLC
3120 East Mission Boulevard* P.O. Box 51478* Ontario, California 91761 U.S.A.
Tel. (909) 923-7300 Fax (909) 923-7400 www.safariland.com