

# Safariland Duty Gear Technical Specification Package

## Model 6360 and 6365

### General Description

Duty Holster for pistol handguns. Designed for use on a Safariland Sam Browne 2 ¼" (58mm) or 2" (50mm) Belt. **6365 has a 1 ½" drop belt loop with jacket slot and for female and male use.** Duty holster includes installed hood guard.

### Product Function

Maintains handgun in a stable, tactically ready configuration, Self Locking System "SLS". Utilizes locking push down thumb platform and rotating hood to reduce take away potential. Also includes an internal locking device that retains the weapon in all directions when the primary device is open. Very easy to re-holster and secure by rotating hood back over handgun with Self Locking Snap-Free operation. Holster uses tension device for handgun adjustment. The adjusting screw is accessed from the opening in the muzzle end of the holster. Belt loop uses new, UBL (Universal Belt Loop) friction style design. Optional Sentry locking device (6001) can be mounted to any SLS system. Sentry provides an additional level of security. To operate the Sentry slide button forward with thumb to engage, slide Sentry back to disengage. Incorporates internal notch to keep lock engaged or disengaged under normal use. Injection molded out of impact resistant nylon.

### Construction Materials

Lamination of polyurethane and synthetic suede non-woven: nylon micro fiber material for holster liner to assist with the protection of the handgun. #207 and #277 nylon cord stitching. Case hardened nylon screws and T-Nuts are used as fastening devices. Polyester elastomer injection molded "SLS" strap with corrosion resistance stainless steel Hardware. Impact resistant reinforced Nylon SLS body. Hi-Carbon tempered steel spring with corrosion resistant film protectant. Must be able to withstand a minimum of 48 hours submerged in water and retain shape and function. Exterior material to pass minimum of 2000 cycles at 1000 gms on taber abrasion test with H18 wheels.

### Available Finishes

Plain, Basketweave, Hi-Gloss, Nylon Look, STX Tactical, STX Plain Black, STX Hi-Gloss

### Available Belt Loops

Standard 2 ¼" (58mm) or 2" (50mm) Universal Belt Loop (UBL)

### Manufacturing Process

Holster body is heat and pressure molded to fit your specified gun with wraparound welt less construction. Sight channel is molded in. Belt loop is injection molded for body curvature.

Dimensions and weights may vary for each gun model.

Dimensions and Weights: 6360 for Glock 17

|         | <u>Imperial</u> | <u>Metric</u> |
|---------|-----------------|---------------|
| Weight: | .75 lbs         | 340.19 g      |
| Length: | 9 ½"            | 24.13 cm      |
| Height: | 3 ¾"            | 9.52 cm       |
| Width:  | 3 ½"            | 8.9 cm        |

### Patent Information

6360/6365 falls under patents: U.S. Pat. #5,501,381 - 5,127,566

### Quality Control

ISO 9001 Societe Generale de Surveillance – ANSI RAB Registrar AQS Quality Procedure.

### Insurance Coverage

Safariland is insured with Product Liability coverage.